



1	REF. SPRINKLER HEADS ARE TO BE WHITE FROM MANUFACTURER IN KITCHEN AND BAR AREA
2	MANUFACTURER HEADS MUST NOT BE PAINTED HEADS MUST BE GARNISHED PINK
3	ALL LIGHT FIXTURES IN LAY-IN CEILING ARE TO BE CENTERED IN ANY DISCREPANCIES
4	ALL DIMENSIONS IN GYPSUM CEILING AND SOFFIT AREAS ARE TO BE FIELD VERIFIED WITH DIMENSIONS SHOWN ARE TO BE FIELD VERIFIED, NOTIFY ARCHITECT OF ANY DISCREPANCIES
5	PROVIDE R-10 BATT INSULATION ABOVE ALL EXISTING AND NEW LAY-IN CEILING SYSTEMS THROUGHOUT
KEYED NOTES: REFLECTED CEILING PLAN	
1	GYPSUM PRYNAVAL CEILING @ 9'-0" AFF. (P3)
2	GYPSUM PRYNAVAL SOFFIT @ 9'-0" AFF. (P1)
3	GARNISHED CEILING @ 10'-0" AFF. (A11)
4	1 1/2" WIDE EXPOSED GRID SYSTEM, 1956 DAW® DOWN BRAND SUSPENSION SYSTEM
5	OPEN TO STRUCTURE ABOVE PIZZA OPEN INSTALLED FOL. FLOOR R-30 INSULATION TO BOTTOM OF STRUCTURE
6	OWNER PROVIDED STAFFED IN TILE TO BE PROVIDED AT ALL LIGHT FIXTURES LOCATIONS WITHIN LAY-IN CEILING AREAS. TYPICAL (M12)
7	3 X 4 IN CEILING TILES @ 12-IN, RANDOMLY ORIENTED AND DISTRIBUTED THROUGHOUT THE SPACE. 2 X 2 IN CEILING TILES TO BE INSTALLED WITH RANDOMLY ORIENTED COORDINATION PATTERN
8	PIZZA OPEN HOOD
9	DISH HOOD
10	TILES MOUNTED VERTICALLY (A11)
11	CLOSE JOINTS BETWEEN TOP OF COOLER AND CEILING WITH LAY-IN CEILING TILES MOUNTED VERTICALLY
12	EXPOSED STRUCTURE
13	EXPOSED STRUCTURE
14	METAL RACK, REFERENCE INTERIOR ELEVATION SHEETS AND SECTIONS
15	CUSTOM WIRE BOTTLE LIGHT FIXTURE, COORDINATE DESIGN WITH TENDANT AND LIGHTING MANUFACTURER
16	APPLY GYPSUM PRYNAVAL TO EXISTING WALTER CEILING FRAMING. PROVIDE EXPOSED FINISH (P1)
17	WIRE EXISTING METAL GRID BEAM WITH GYPSUM PRYNAVAL EXTEND VERTICALLY TO BOTTOM OF WALTER CEILING FRAMING. TRIM PER INTERIOR ELEVATIONS. FIELD VERIFY HEIGHT.
18	GYPSUM PRYNAVAL SOFFIT @ 11'-0" AFF. FIELD VERIFY HEIGHT COORDINATE WITH TENDANT AND ADJACENT TRIM FINISHES PER INTERIOR ELEVATIONS
19	REMOVE EXISTING WALTER FRAMING AT PERIMETER OF COFFERED CEILING. LEAVE ALL OTHER EXISTING FRAMING AND HEEP AREA AS REQUIRED TO RECEIVE NEW LAY-IN CEILING
20	INSTALL GYPSUM PRYNAVAL OVER EXISTING SOFFIT FRAMING AT 11'-0" AFF.
21	INSTALL GYPSUM PRYNAVAL OVER EXISTING SOFFIT FRAMING AT 12'-0" AFF.
22	GYPSUM PRYNAVAL SOFFIT @ 11'-0" AFF.
23	SQUARE GUIDELINE FOR LIGHTING LAYOUT. REFERENCE MARKER ONLY
24	LIGHTING PER ELECTRICAL COORDINATE WITH TENDANT AND ELECTRICAL DRAWINGS
25	3 X 4 IN CEILING TILES @ 12-IN, RANDOMLY ORIENTED AND DISTRIBUTED THROUGHOUT THE SPACE. 2 X 2 IN CEILING TILES TO BE INSTALLED WITH RANDOMLY ORIENTED COORDINATION PATTERN
26	COORDINATE WITH INTERIOR ELEVATIONS
27	INSTALL GYPSUM PRYNAVAL OVER EXISTING METAL GRID FRAMED SOFFIT @ 12'-1" AFF. PROVIDE TRIM PER INTERIOR ELEVATIONS. FIELD VERIFY HEIGHT.
28	GYPSUM PRYNAVAL CEILING @ 9'-0" AFF.